FOREIGN TECHNOLOGY DIVISION



STUDY OF ADDITIVES SYNTHESIZED FROM DERIVATIVES OF NAPHTHENIC HYDROCARBONS

bу

I. M. Orudzheva and Sh. M. Novruzov



500 i 19**6**9

Distribution of this document is unlimited. It may be released to the Clearinghouse, Department of Commerce, for sale to the general public.

Reproduced by the CLEARINGHOUSE for Federal Scientific & Technical Information Springfield Va 22151

EDITED TRANSLATION

STUDY OF ADDITIVES SYNTHESIZED FROM DERIVATIVES OF NAPHTHENIC HYDROCARBONS

By: I. M. Orudzheva and Sh. M. Novruzov

English pages: 4

SOURCE: Azerbaydzhanskoye Neftyanoye Khozyaystvo

(Azerbaydzhan Petroleum Economy), 1965,

pp 37-38.

Translated by: F. Dion/TDBRO-2

TT7002329

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ABVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REPLECT THE POSITION OR OPINION OF THE POREIGN TECHNOLOGY DIVISION.

PREPARED BY

TRANSLATION DIVISION
FOREIGN TECHNIQLOGY DIVISION
WP-APB, OHIO.

FTD- HT - 23-1252-67

Dete15 Dec. 19 67

DATA HANDLING PAGE					
O PACCESSION NO.	96-DOCUMENT LOC	30-TOPIC TAGS			
TT7002329		antioxidant additive, lubricating oil			
SYNTHE STUDY O SYNTHESIZED F DERIVATIVES O HYDROCARBONS	ROM				
47-SUBJECT AREA					
11			•		
43-AUTHOR/00-AUTHORS ORUDZHEVA, I.		M.; NOVRUZOV, SH. M.			
49-SOURCE				58-DOCUMENT NO.	
AZERBAYDZHANS:	KOYE NEFTYANOYE	KHOZYAYSTVO	(RUSSIAN)	FTD-HT-23-1252-67	
	WNGRADING INFORMATIO		1	72301-78	
UNCL, O			NONE	UNCL	
76-REEL/FRAME NO.	77-SUPERSEDES	76-CHANGES	40-GEOGRAPHICAL AREA	NO. OF PAGES	
1883 0701	ļ	;	UR	4	
CONTRACT NO.	X REF ACC. NO.	PUBLISHING DATE	TYPE PRODUCT	REVISION FREQ	
	AR6024954		Translation	n None	
UR/0000	765 /000/000/003	770029	ACCESSION NO. TT7002329		
ABSTRACT In order to develop antioxidant motor-oil additives whose composition includes phosphorus and sulfur, monochlorides of cyclohexyl- and methylcyclohexylphosphorous acids were prepared. The chlorides obtained were subjected to condensation reactions with various alkyl phenols (C ₃ -C ₁₀) and sulfide-disulfide alkyl phenols. The effect of the synthesized compounds on the performance characteristics of D-11 oil was investigated. Tests of these compounds for the oxidation resistance, thermal stability, and anticorrosive properties of the diesel oil showed that the induction period of the oxidation, determined by the method of the AzNII, increases from 30 to 70-100 min, and the time of absorption of 10 ml of oxygen, from 240 to 340-355 min. The anticorrosive properties were tested under drastic conditions (method of NAMI); in the presence of the additives, the corrosion decreases from 360 to 1-13 g/m². The thermal stability of D-11 oil increases from 25 to 60-105 min. Phosphorus- and sulfur-containing compounds in compounds in combination with SB-3 and BFK additives have practically no effect on the wetting properties of the oils.					

AFSC AUG 4 (Test form under revision)

STUDY OF ADDITIVES SYNTHESIZED FROM DERIVATIVES OF NAPHTHENIC HYDROCARBONS

I. M. Orudzheva and Sh. M. Novruzov

To obtain antioxidant additives to motor oils we synthesized P- and SP-containing compounds. Cyclohexanol and methylcyclohexanol were taken as the initial raw materials. The reaction of these alcohols with phosphorus trichloride produced the corresponding monochlorides of cyclohexyl and methylcyclohexyl phosphorous acids.

The synthesized acid chlorides were subjected to condensation with various alkyl phenols ($^{\rm C}_3$ - $^{\rm C}_{10}$), and as a result a series of triply substituted phosphites was obtained.

These phosphites contain 5.8-9.2% phosphorus. We obtained P-containing additives, for which the monochlorides of dicyclohexyl phosphorous acid were reacted with sulfide-disulfide alkyl phenols. The characteristics of the obtained P- and PS- containing additives are given in Table 1.

We studied the effect of these compounds on the performance characteristics of D-11 oil. Mixed with the new additives, D-11 oil was tested for stability, thermal stability and anticorrosion properties.

The results of these tests are given in Tables 2 and 3.

From the data of Table 2 it is evident that in small concentrations (about 0.1%) the phosphites very effectively improve the stability of oils (as determined by the AzNII method) at 175°C. The induction period of oxidation increases from 30 to 70-100 min, and the time for absorption of 10 ml of oxygen, from 240 to 340-355 min.

All the synthesized compounds increase the stability of D-11 oil identically. An analogous picture is observed in the tests of these for anticorrosion properties and thermal stabiltiy (Table 3).

Table 1. Elementary Composition of Compounds Synthesized from Naphthenic Hydrocarbons

	Content, %				
Proposed Formula	Carbon	Hydro- gen	Phos- pho- rous	Sulfur	
(C6H110-)2POC6H4C3H7	69.37	8.95	9.20		
(сн ₃ с ₆ н ₁₀ о-) ₂ Рос ₆ н ₄ с ₃ н ₇	70.68	9.83	7.56		
(CH ₃ C ₆ H ₁₀ C-) ₂ POC ₆ H ₄ C ₄ H ₉	70.48	9.23	7.89		
(C6H110-)2POC6H4C5H11	70.62	9.54	7.90		
(C6H110-)2POC6H4C16H21	73.02	10.36	5.84		
(C ₆ H ₁₁ O-) ₂ P P(-OC ₆ H ₁₁) ₂ O O H ₇ C ₃ -C ₆ H ₃ -S-C ₆ H ₃ -C ₃ H ₇	66.91	7.90	8.54	4.83	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	66.79	8.10	7.32	3.94	
(C ₆ H ₁₁ O-) ₂ P P(-OC ₆ H ₁₁) ₂ O O H ₁₁ C ₅ -C ₆ H ₃ -S-C ₆ H ₃ -C ₅ H ₁₁	66.97	9.42	6.90	3.51	
$\frac{(c_{6}H_{11}O-)_{2}P}{O} = \frac{P(-OC_{6}H_{11})_{2}}{O}$	64.86	8.50	8.06	6.94	
(C ₆ H ₁₁ O-) ₂ P P(-OC ₆ H ₁₁) ₂ O O H ₁₁ C ₅ -C ₆ H ₃ -S ₂ -C ₆ H ₃ -C ₅ H ₁₁	65.83	8.00	7.69	7.00	

Table 2. Stability of D-11 Oil Mixed with Different Antioxidant Additives by the AzNII Method

Sample	Quantity of Additive,	Induc- tion Period, min	Time for Absorption of 10 ml of Oxygen, min
Oil Without Additive Oil + Additive No. 1 Oil + Additive No. 2 Oil + Additive No. 2 Oil + Additive No. 3 Oil + Additive No. 4 Oil + Additive No. 5 Oil + Additive No. 5	0.1 0.05 0.3 0.1 0.1 0.1 0.05	30 63 93 95 108 77 76	240 335 354 355 341 341 354 321

Table 3. Effect of P- and S-Containing Compounds on the Anticorrosion and Thermal-Stability Properties

		-1 -14-			
Sample	Quantity of Addi- tive, %	Thermal Oxidation Resis- tance by the Papol	Klentior Laguer Deposi-	Laquer Residue,	Corrosion NAMI Method, 25 h, g/m
Oil Without Additive Oil + Additive No. 1 Oil + Additive No. 1 Oil + Additive No. 4 Oil + Additive No. 4 Oil + Additive No. 5 Oil + Additive No. 5 Oil + Additive No. 6 Oil + Additive No. 7 Oil + Additive No. 7 Oil + Additive No. 8 Oil + Additive No. 9 Oil + Additive No. 9	0.5 1.0 0.5 1.0 0.5 1.0 1.0 1.0	25 50 98 57.5 105.2 94 74 75 73 53	_	22 9.5 8 14 6 14 9 13 12 10.5	27.0 1.65 4.65 5.0 8.7 6.35 6.0

Table 4. Wetting Properties of D-11 Oil with Additives by the PZV Method

Sample	Wetting Properties, Units		
Oil Without Additive Oil + 5% SB-3 Oil + 6% BFK Oil + 5% SB-3 + 1% Additive No. 8 Oil + 6% BFK + 1% Additive No. 8 Oil + 6% BFK + 1% Additive No. 4	5 to 5.5 1 to 1.5 0.5 to 1.0 0.5 0.5 0 to 0.5		

The anticorrosion properties of D-11 oil were tested under drastic conditions by the NAMI method for 25 h in the presence of a catalyst, copper petronate. When 0.5-1.0% of the P-containing compounds are added to D-11 oil corrosion of the oil is reduced from 360 to 1-13 g/m². The phosphites also effectively increase the thermal stability of D-11 oil and reduce the coefficient of laquer deposition (Table 3).

P- and S-containing compounds produced from cyclohexanol and containing 6.9-8.5% P and 3.5-6.9% S incrase the thermal stability of D-11 oil and improve its anticorrosion properties (Table 3). In combination with SB-3 and BFK additives these compounds do not worsen the wetting properties of diesel oil (Table 4).

Thus, from derivatives of naphthenic hydrocarbons we synthesized a number of new S- and P-containing compounds that in pure form and in combination with other known multipurpose additives improve the performance characteristics of oils.